



Category: Power Generators

Volvo Penta TAD1343GE 385 kVA Genset

Ratings & Electrical

- Prime Power: 308 kW / 385 kVA
- Standby Power: ~338 kW / 420 kVA
- Frequency: 50 Hz
- Speed: 1500 rpm
- Voltage: 400/230 V (3-phase)
- Power Factor: 0.8 (lagging)
- Alternator Insulation: Class H
- Voltage Regulation: $\pm 1\%$

Engine / Mechanical

- Engine Model: Volvo TAD1343GE
- Configuration: 4-stroke, 6-cylinder, inline, turbocharged & aftercooled
- Displacement: 9.5 L

- Bore × Stroke: 108 mm × 130 mm
- Compression Ratio: 17.5 : 1
- Lubricating Oil Capacity: ~32 L
- Coolant Capacity: ~45 L

Fuel & Consumption

- Fuel Type: Diesel
- Fuel Consumption @100% Load: ~75 L/h
- Fuel Consumption @75% Load: ~56 L/h
- Fuel Tank Capacity: ~850 L (typical enclosure)

Cooling, Exhaust & Air

- Exhaust Gas Temperature: ~510 °C
- Exhaust Gas Flow: ~38 m³/min
- Max Exhaust Back Pressure: 10 kPa
- Cooling System: Radiator-cooled, tropical rating

Physical Dimensions & Weight

- Dimensions (L × W × H): ~3500 mm × 1700 mm × 2100 mm
- Weight (approx.): ~3500 kg (open set)

Alternator & Control

- Alternator Frame: Stamford or equivalent, Class H insulation
- Control Panel: Volvo/DeepSea electronic controller
- Features: Monitoring, protection & optional auto-start/stop