



Category: Power Generators

Volvo Penta TAD1643GE 660 kVA Diesel Power Generator

Ratings & Electrical

- Prime Power: 528 kW / 660 kVA
- Standby Power: ~580 kW / 725 kVA
- Frequency: 50 Hz
- Speed: 1500 rpm
- Voltage: 400/230 V (3-phase)
- Power Factor: 0.8 (lagging)
- Alternator: Stamford or equivalent, Class H insulation
- Voltage Regulation: $\pm 1\%$

Engine / Mechanical

- Engine Model: Volvo Penta TAD1643GE
- Configuration: 4-stroke, 6-cylinder, inline, turbocharged & aftercooled
- Displacement: 14.0 L
- Bore × Stroke: 132 mm × 150 mm
- Compression Ratio: 17.5 : 1
- Lubricating Oil Capacity: ~55 L
- Coolant Capacity: ~70 L

Fuel & Consumption

- Fuel Type: Diesel
- Fuel Consumption @100% Load: ~150 L/h
- Fuel Consumption @75% Load: ~113 L/h
- Fuel Tank Capacity: ~1300 L (typical enclosure)

Cooling, Exhaust & Air

- Exhaust Gas Temperature: ~540 °C
- Exhaust Gas Flow: ~60 m³/min
- Max Exhaust Back Pressure: 10 kPa
- Cooling System: Radiator-cooled, tropical rating

Physical Dimensions & Weight

- Dimensions (L × W × H): ~4100 mm × 2000 mm × 2350 mm
- Weight (approx.): ~5500 kg (open set)

Control

- Control Panel: Volvo/DeepSea electronic controller
- Features: Monitoring, protection & optional auto-start/stop