




Category: Power Generators

Cummins C380D5 6LTAA9.5-G1 380 kVA Power Generator

Ratings & Electrical

- Prime Power: 304 kW / 380 kVA
- Standby Power: ~334 kW / 418 kVA
- Frequency: 50 Hz
- Speed: 1500 rpm
- Voltage: 400/230 V (3-phase)
- Power Factor: 0.8 (lagging)
- Alternator Insulation: Class H
- Voltage Regulation: $\pm 1\%$

Engine / Mechanical

- Engine Model: Cummins 6LTAA9.5-G1
- Configuration: 4-stroke, 6-cylinder, inline, turbocharged & aftercooled
- Displacement: 9.5 L
- Bore × Stroke: 114 mm × 135 mm
- Compression Ratio: 16.5 : 1
- Lubricating Oil Capacity: ~50 L
- Coolant Capacity: ~65 L

Fuel & Consumption

- Fuel Type: Diesel
- Fuel Consumption @100% Load: ~125 L/h
- Fuel Consumption @75% Load: ~94 L/h
- Fuel Tank Capacity: ~1100 L (typical enclosure)

Cooling, Exhaust & Air

- Exhaust Gas Temperature: ~565 °C
- Exhaust Gas Flow: ~42 m³/min
- Max Exhaust Back Pressure: 10 kPa
- Cooling System: Radiator-cooled, tropical rating

Physical Dimensions & Weight

- Dimensions (L × W × H): ~4100 mm × 1850 mm × 2350 mm
- Weight (approx.): ~4200 kg (open set)

Alternator & Control

- Alternator Frame: Stamford or equivalent, Class H insulation
- Control Panel: Cummins/DeepSea electronic controller
- Features: Monitoring, protection & optional auto-start/stop